



TECHNICAL PAINT SERVICES

A1001 MAGNETISM SENSITIVE PAINT

Features:

A pure nickel based metallic preparation which when dry, in sufficient thickness, will attract permanent magnets to itself. Can be used on most surfaces which are non-ferrous, thus obviating the need to hang steel sheeting.

Availability:

In 5, 2.5 and 1 Litre containers in Dark Grey. Can be over painted with 1 thin coat of oil based paints to change the colour, but care must be taken so as to avoid thick over coating, as this detracts from the coating's ability to work properly.

Volume Solids:

85% ± 3% (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from corrosion, dust and grease. Can be applied to most primed substrates including wood, plaster, cement, various metals and plastic.
PLEASE CONSULT WITH OUR TECHNICAL DEPARTMENT TO CONFIRM.

Application:

By brush only, using 3 - 4 heavy coats, with suitable drying in between applications. Do not thin.

Coverage:

Use 1 Litre to cover 1 square metre, using 3 or 4 coats @ 80 microns minimum dry film thickness per coat.

Drying:

Hard dry & recoatable: 16 hours @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.