



TECHNICAL PAINT SERVICES

A113 POLYURETHANE ONE PACK FINISH

Features:

A high quality finishing paint based on urethane-modified alkyd resin, exhibiting good exterior durability and colour retention, suitable for application to wood, steel and weathered concrete.

Availability:

BS4800 colour range in 5, 2.5 and 1 Litre containers.

Volume Solids:

57% ± 3% (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from corrosion, dust and grease. Concrete must be at least 6 months old before application of A113. For application on to ferrous surfaces use AP79 Universal Primer, on aluminium use UP88 One Pack Etching Primer and on plastic use PP129 Adhesion Promoter.

Application:

By brush or roller. Supplied ready for use for brushing. Use X156 White Spirit for cleaning.

Coverage:

Approximately 40 - 50 sq metres per 5 Litres depending on porosity of the substrate.

Drying:

Touch dry: 1 hour @ 20°C.

Hard dry & recoatable: 6 hours @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.