



# TECHNICAL PAINT SERVICES

## A146/5 SOLAR REFLECTING SPIRIT WHITE

**Features:**

A fast drying, spirit based solar reflecting finish suitable for application to tarmac, concrete, asphalt and glass. Extremely durable and resistant to asphalt “bleeding”.

**Availability:**

In 5, 2.5 and 1 Litre containers.

**Volume Solids:**

42% ± 3% (BS 3900 Part A10).

**Preparation:**

The substrate must be thoroughly clean, dry and free from dust and grease.

**Application:**

Brush, roller, or conventional spray. Supplied ready for use for brushing and rolling. Thin up to 25% by volume, using ATR96 Spirit Thinners to achieve a spraying viscosity of 25 - 40 seconds BSB4 cup @ 20°C.

**Note:**

When rolling, check resistance of roller to Methylated Spirit. Ensure paint is evenly distributed without over-loading when rolling.

**Coverage:**

Approximately 30 - 40 sq metres per 5 Litres, depending on porosity of the substrate.

**Drying:**

Touch dry: 15 - 30 minutes @ 20°C.

Recoatable: 30 minutes @ 20°C.

Hard dry: 1 hour @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.  
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.