



# TECHNICAL PAINT SERVICES

## A3 SOLVENT BASED ANTI-CONDENSATION PAINT

### **Features:**

A thixotropic textured paint which dries to provide an anti-corrosive, acoustically insulating and absorbent finish. Designed to reduce or eliminate condensation on steel, brick, concrete, plaster and various metals by forming an insulating layer.

### **Availability:**

All BS4800 colour range in 5 Litre containers only.

### **Volume Solids:**

50% ± 3% (BS 3900 Part A10).

### **Preparation:**

The surface should be thoroughly clean, dry and free from corrosion, dust and grease. Oil based paints should be stripped using X16 Stripper Water Wash, or sealed with AL124/70/1 Varnish Meth's Isolator.

### **Application:**

Brush. To obtain a good key, apply by stippling the first coat onto a suitably primed surface, then build up by further application. A3 may be applied over RL10/70/1 Chlorinated Rubber Sealer, EL56/70 Emulsion Sealer, AP79 Universal Primer, AP83/65 Zinc Rich Galvanic Primer, UP89 Two Pack Etching Primer or AP114 Two Pack Epoxy Primer.

### **Coverage:**

Approximately 3 - 4 sq metres per 5 Litres giving a dry film thickness of 250 microns after 3 - 4 coats.

### **Drying:**

Touch Dry: 15 minutes @ 20°C.

Recoatable: 2 hours @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.

See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.