



TECHNICAL PAINT SERVICES

A38 EPOXY ESTER FLOOR FINISH

Features:

A quick drying, high opacity floor finish which has excellent resistance to abrasion, oil, petrol, detergent, and diluted chemical solutions. Epoxy Ester Floor Finish also has excellent adhesion to most substrates, especially concrete, metal and wood. It may be applied to existing painted surfaces without reacting. This paint should not be applied over PVA sealer, latex self leveling compound or power floated concrete. Please contact our Technical Department.

Availability:

All BS4800 colours plus Clear in 5, 2.5 and 1 Litre containers.
A39 Epoxy Ester Floor Finish Non-Slip is also available.

Volume Solids:

53% ± 3% (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from dust, corrosion and grease. Concrete floors must be at least 6 months old before painting. If the floor is very porous or dusting badly, it is advisable to apply a priming coat of A38 thinned 15 - 20% by volume with X156 White Spirit. For newer concrete, please contact our Technical Department.

Application:

By brush or roller. Supplied ready for use for brushing. If required, thin up to 20% with X156 White Spirit, or ATR154 Synthetic Brushing Thinner.

Coverage:

Approximately 40 sq metres per 5 Litres per coat.

Drying:

Touch dry:	4 hours @ 20°C.
Hard dry:	12 hours @ 20°C.
Recoatable:	Overnight.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.