



TECHNICAL PAINT SERVICES

A96 SPIRIT ROADLINE FINISH

Features:

An extremely fast drying, durable finish suitable for application to concrete, tarmac, wood and most other surfaces. A96 exhibits excellent resistance to water, petrol, oil, grease and weak battery acid, and is also effective as a barrier coat where oil and grease stains on bitumastic surfaces have to be over-coated.

Availability:

White, Black and Yellow in 5, 2.5 and 1 Litre containers. Other colours available to order.

Volume Solids:

55% ± 3% (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from dust and grease, although A96 will tolerate the presence of oil and grease stains.

Application:

Brush, roller or conventional spray. When rolling, check resistance of roller to Methylated Spirits. When brushing, apply with a lacquering action using as wide a brush as possible, as the finish is extremely fast drying. For spray application, thin up to 20% by volume with ATR96 Spirit Thinners to achieve a spraying viscosity of 25 - 30 seconds BSB4 cup @ 20°C.

Coverage:

30 sq metres per 5 Litres per coat @ 30 microns dry film thickness.

Drying:

Touch dry: 5 - 10 minutes @ 20°C.

Hard dry: 1 hour @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.