



TECHNICAL PAINT SERVICES

AG1 CONTRACT BITUMINOUS COLOURS

Features:

A budget blend of refined bitumen and alkyd resins, designed to give good water proofing qualities for large structural steel items, farm buildings, tanks, silos etc.

Availability:

5 & 10 Litre containers in the BS4800 range of colours.

Volume Solids:

50% ± 3% (BS 3900 Part A10). Will vary with colour.

Preparation:

The substrate must be thoroughly clean, dry and free from oil and grease. May be applied directly to cleaned surfaces. Extended durability may be achieved by the use of AP79 Universal Primer prior to finishing.

Application:

Brush, roller, conventional or airless spray. Use UTR112 Universal Synthetic Thinners if required. Clean equipment with X156 White Spirit or X155 Turps substitute.

Coverage:

Approximately 40 sq metres per 5 Litres per coat, when brushed.

Drying:

Touch dry: 30 minutes.

Recoatable: 12 hours @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.