



# TECHNICAL PAINT SERVICES

## AL113 POLYURETHANE ONE PACK VARNISH

### **Features:**

A high quality single pack polyurethane varnish which exhibits outstanding toughness and wear resistance, but does not have the drawbacks of short pot life encountered with Two Pack or moisture cured Polyurethane. Ideal for use on all types of wooden furniture, wood and concrete floors.

### **Availability:**

In 5, 2.5 and 1 Litre containers. Gloss, semi gloss and eggshell.

### **Volume Solids:**

43% ± 3% (BS 3900 Part A10).

### **Preparation:**

The substrate must be thoroughly clean, dry and free from corrosion, dust and grease. Timber surfaces should be sanded to a smooth finish and any wax removed with X156 White Spirit. Two applications may be necessary on wood which has been waxed frequently. Concrete must be at least 6 months old before coating.

### **Application:**

By brush, roller or squeegee. Supplied ready for use for brushing. Use X156 White Spirit for cleaning and thinning if required. On unvarnished wood (including worn surfaces), apply a sealer coat thinned up to 20% by volume with X156 White Spirit and two un-thinned coats. Rubbing down between coats is not necessary if applied at 24 hour intervals.

### **Coverage:**

Approximately 50 - 60 metres per 5 Litres depending on porosity of substrate.

### **Drying:**

Touch dry: 1 hour @ 20°C.  
Hard dry: 2 hours @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.  
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.