



TECHNICAL PAINT SERVICES

AL122/70/1 SYNTHETIC LACQUER FOR COPPER AND BRASS

Features:

A non-yellowing, water white acrylic lacquer, exhibiting excellent adhesion to most metals and with good flexibility and U.V. resistance. Suitable for application to silver plate, brass, copper and aluminium.

Availability:

In 5, 2.5 and 1 Litre containers.

Volume Solids:

45% ± 3% (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from corrosion, dust and grease.

Application:

By conventional spray or dipping although small areas may be brushed. Thin up to 20% by volume with UTR112 Universal Synthetic Thinners to achieve a spraying viscosity of 20 - 30 seconds BSB4 cup @ 20°C.

Coverage:

Approximately 60 metres per 5 Litres at 25 microns dry film thickness.

Drying:

Touch dry: 30 minutes @ 20°C.

Hard dry: 1 hour @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.