



TECHNICAL PAINT SERVICES

AS56/5 ALKALI RESISTING PRIMER, OFF-WHITE

Features:

A specially formulated primer, based on alkyd resin, which resists the alkali present in new concrete and plaster. It is also suitable as a sealer for asbestos and cement sheeting.

Availability:

In 5.0 and 2.5 Litre containers.

Volume Solids:

51% ± 3% (BS 3900 Part A10).

Preparation:

The substrate should be thoroughly clean, dry and free from dust and grease. Concrete and plaster must be at least 7 days old. Lime wash, distemper or cementitious paints must be removed before application of the primer.

Application:

Brush or conventional spray. Supplied ready for use for brushing. For spraying, thin up to 5% by volume with X156 White Spirit.

Coverage:

Approximately 40 - 60 sq metres per 5.0 Litres depending on porosity of substrate.

Drying:

Touch dry: 4 hours @ 20°C.

Recoatable with oil based or emulsion paints after overnight drying.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

AS565 Rev 07 2011

27 SOUTHCOTE ROAD BOURNEMOUTH BH1 3SH Tel 0845 230 1244 Fax 0845 230 1255
Email enquiries@technicalpaintservices.co.uk www.technicalpaintservices.com

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.