



TECHNICAL PAINT SERVICES

E4 WATER BASED ANTI-CONDENSATION PAINT TEXTURED

Features:

A thixotropic textured paint, which dries to provide an acoustically insulating and absorbent finish. Designed to reduce or eliminate condensation on steel, brick, concrete, plaster and various metals forming an insulating layer.

Availability:

All BS4800 colour range in 5 Litre containers.

Volume Solids:

40% ± 3% (BS 3900 Part A10).

Preparation:

The surface should be thoroughly clean, dry and free from dust, oil and grease.

Application:

By brush. To obtain a good key, apply by stippling the first coat onto a suitably primed surface, then build up by further application. E4 may be applied over RL10/70/1 Chlorinated Rubber Clear Sealer, EL56/70 Emulsion Sealer, E27/5/4 Emulsion 100% Acrylic White or AP79 Metal Primer.

Coverage:

Approximately 5 sq metres per 5 Litres, giving a dry film thickness of 250 microns, after 3 - 4 coats.

Drying:

Hard dry & recoatable: 6 hours @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.