



TECHNICAL PAINT SERVICES

ES27/70/4 EMULSION 100% ACRYLIC CLEAR

Features:

A water based sealer, stabiliser and barrier coat based on acrylic copolymer. Suitable for application to exterior brickwork, masonry, asbestos and other porous surfaces. Also suitable as an isolator for use between two incompatible materials. Dries to a clear, satin or gloss finish. It acts as a sacrificial anti-graffiti glaze over existing paints.

Availability:

5, 2.5 and 1 Litre containers.

Volume Solids:

60% ± 3% (BS 3900 Part A10).

Preparation:

The surface should be thoroughly clean, dry and free from dust and grease.

Application:

Brush or roller. Use clean tap water for thinning and cleaning. To aid penetration of absorbent surfaces, it is recommended that a first coat is applied thinned up to 50% by volume with clean tap water.

Coverage:

Approximately 40 - 50 sq metres per 5 Litres depending on porosity of substrate.

Drying:

Touch dry: 30 minutes @ 20°C.

Hard dry & recoatable: 2 hours @ 20°C.

Thorough drying is indicated by the original opaque appearance becoming clear.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.