



TECHNICAL PAINT SERVICES

ET27 TEXTURED BASECOAT

Features:

A water based acrylic thixotropic textured heavy bodied basecoat. For use on portakabins, mobile homes etc. It is suitable for application to all types of porous substrates, wood, concrete etc. Formulated to give a high or low relief stipple finish according to the method of application. Must be over coated with E27 Acrylic Finish.

Availability:

Natural Off White only in 5 Litre containers in Matt finish.

Volume Solids:

45% ± 3% (BS 3900 Part A10).

Preparation:

The surface should be thoroughly clean, dry and free from dust and grease. Previously painted surfaces must be stripped, thoroughly rubbed down with abrasive paper and cleaned prior to application.

Application:

By stipple brush or roller. Supplied ready for use. Do not thin. A high stipple relief can be obtained by placing a sponge in a plastic bag and pulling out the points. Sharp points can be flattened by using a flat trowel. It is recommended that one or two coats are applied to previously untreated surfaces, allowing 8 hours drying between coats. Clean all tools in clean water.

Coverage:

Approximately $\frac{3}{4}$ sq metres per 5 Litres depending on porosity of substrate.

Drying:

Touch dry: 1 - 2 hours @ 20°C.

Hard dry & recoatable: 8 hours @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.