



TECHNICAL PAINT SERVICES

H45/60 HEAT RESISTING QUICK DRYING BRIGHT ALUMINIUM

Features:

A general purpose, quick drying, bright aluminium paint with excellent heat resistance up to 250°C. Suitable for application to ferrous metals and timber.

Availability:

5, 2.5 and 1 Litre containers.

Volume Solids:

55% ± 3% (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from corrosion, dust and grease. For optimum durability it is recommended that ferrous substrates are treated with UP89 Two Pack Etching Primer prior to application of H45/61.

Application:

Do not apply to heated surfaces, cool before applying by conventional or airless spray. Small areas may be brushed. Thin up to 20% by volume, using UTR112 Universal Synthetic Thinners to achieve a spraying viscosity of 25 - 30 seconds BSB4 cup @ 20°C.

Note:

Some difference in brightness and general appearance can be anticipated between brush and spray application and therefore mixed methods of application are not recommended.

Coverage:

Approximately 60 sq metres per 5 Litres depending on surface.

Drying:

Touch dry: 5 - 8 minutes @ 20°C.
Hard dry: 40 - 45 minutes @ 20°C.
Full properties: 7 days.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.