



TECHNICAL PAINT SERVICES

H46/60 LOW TEMPERATURE HEAT RESISTING ALUMINIUM

Features:

A synthetic resin based bright aluminium finish, ideally suited to the coating of flues and boilers. Provides a durable, water resistant finish capable of withstanding temperatures up to 180°C.

Availability:

5, 2.5 and 1 Litre containers.

Volume Solids:

50% ± 3% (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from corrosion, dust and grease.

Application:

Do not apply to heated surfaces, cool before applying by brush, roller, conventional or airless spray. Thin up to 20% by volume, using UTR112 Universal Synthetic Thinners to achieve a spraying viscosity of 25 - 30 seconds BSB4 cup @ 20°C. Two coats are recommended to achieve a minimum dry film thickness of 50 microns.

Coverage:

Approximately 35 - 40 sq metres per 5 Litres depending on surface profile.

Drying:

Touch dry: 3 - 4 hours @ 20°C.

Hard dry & recoatable: Overnight.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.