



TECHNICAL PAINT SERVICES

ML55/70/1 YACHT VARNISH

Features:

A high quality varnish based on alkyd resin, specially formulated to meet the exacting demands of a marine environment. This varnish has excellent resistance to intense sunlight and salt water, whilst providing a durable, protective coating and enhancing the natural appearance of wood.

Availability:

In 5, 2.5 and 1 Litre containers.

Volume Solids:

53% ± 3% (BS 3900 Part A10). May vary with colour.

Preparation:

The substrate must be thoroughly clean, dry and free from dust and grease. Remove any wax with X156 White Spirit and sand down to a smooth finish.

Application:

Brush, roller or squeegee. Supplied ready for use for brushing. Use X156 White Spirit for cleaning. On previously untreated wood, it is advisable to thin the first coat up to 20% by volume with X156 White Spirit to aid penetration and seal the wood. It is recommended that two coats are applied to sealed wood.

Coverage:

Approximately 60 sq metres per 5 Litres per coat.

Drying:

Touch dry: 3 hours @ 20°C.

Hard dry: 8 hours @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.