



# TECHNICAL PAINT SERVICES

## MSP1009 MULTI SURFACE PRIMER

### **Features:**

An extremely fast drying, durable primer, suitable for application to most common “un-paintable” surfaces including glass, ceramic tiles, stainless steel, copper, brass, old varnished wood, plastics and many more. It has excellent adhesion properties allowing a suitable top coat to be applied and is also effective as a barrier coat where unknown contaminants are present.

### **Availability:**

White only in 5, 2.5 and 1 Litre containers.

### **Volume Solids:**

55% ± 3% (BS 3900 Part A10).

### **Preparation:**

We recommend the substrate is thoroughly clean, dry and free from dust and grease, although MSP1009 will tolerate the presence of oil and grease stains.

### **Application:**

Brush or roller. When rolling, check resistance of roller to X152 Methylated Spirits. When brushing, apply with a lacquering action using as wide a brush as possible, with as little over-brushing as possible, as the finish is extremely fast drying. Use only X152 Methylated Spirits for the cleaning of tools and equipment.

### **Coverage:**

40 sq metres per 5 Litres per coat @ 30 microns dry film thickness.

### **Drying:**

Touch dry:	30 - 40 minutes @ 20°C.
Hard dry:	2 hours @ 20°C.
Light foot traffic:	4 - 5 hours @ 20°C.
Recoatable:	16 - 24 hours @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.  
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.