



TECHNICAL PAINT SERVICES

PP129 ADHESION PROMOTER/PRIMER

Features:

A single pack adhesion promoter suitable for use on most types of thermoplastic, including polyurethane, polyamide, nylon, polypropylene, ethylene-diene rubber, G.R.P. (fibreglass), polycarbonate, A.B.S., polybutene, terephthalate and polyphenylene oxide. PP129 can be over-coated with any solvent based (non-water) paint system. NOT SUITABLE FOR POLYETHYLENE.

Availability:

Clear in 5, 2.5 and 1 Litre containers.

Volume Solids:

15% ± 3% (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from dust and grease. It is advisable to abrade the surface before application.

Application:

Brush or conventional spray. Supplied ready for use.

Coverage:

Approximately 20 sq metres per 1 Litre.

Drying:

Touch dry: 20 minutes @ 20°C.

Recoatable: 1 hour @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.

27 SOUTHCOTE ROAD BOURNEMOUTH BH1 3SH Tel 0845 230 1244 Fax 0845 230 1255
Email enquiries@technicalpaintservices.co.uk www.technicalpaintservices.com

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.