



# TECHNICAL PAINT SERVICES

## R22 ELASTIC FINISH

**Features:**

A specially formulated, quick drying and extremely flexible paint that provides a durable waterproof finish for rubber, leather, plastic and canvas.

**Availability:**

BS4800 range of colours plus Transparent, in minimum of 5 Litres.

**Volume Solids:**

55% ± 3% (BS 3900 Part A10).

**Preparation:**

The surface should be clean, dry and free from dust and grease. If the surface has a glossy sheen, this should be reduced by flattening to improve adhesion. When applying to plastic substrates, test compatibility by applying to a small area and check for satisfactory drying.

**Application:**

Brush, conventional spray or dipping. Supplied ready for use for brushing. Thin up to 20% by volume with RTR22 Elastic Thinners to achieve a satisfactory spraying viscosity.

**Coverage:**

40 - 50 sq metres per 5 Litres at 20 microns dry film thickness.

**Drying:**

10 - 15 minutes @ 20°C. On some plastic substrates, drying may be retarded due to reaction with Plasticiser.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.  
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

**FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.**