



TECHNICAL PAINT SERVICES

WB1005 LIME PAINT

Features:

A traditional semi- prepared paint. For use on walls with no damp-proofing that need to breathe water vapour in and out such as Cobb construction or cellars. Gives a pleasing low sheen. Hygienic but non-washable.

Availability:

5 Litre containers in Natural White. Other colours made to order in minimum 25 Litre lots.

Volume Solids:

60% + 3% (BS 3900 Part A10).

Preparation:

Surface should be clean and can be slightly damp but not wet. Mix 10 - 20% clean water with WB1005 and stir thoroughly to make a thin primer for very porous surfaces, otherwise use neat.

Application:

One to two coats by brush only. We recommend that protective clothing, gloves and eye protection be used during application of WB1005.

Coverage:

Approximately 20 - 30 sq metres per 5 Litres.

Drying:

Touch dry:	24 hours @ 20°C.
Recoatable:	48 hours @ 20°C.
Fully cured:	up to 7 days @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.