



TECHNICAL PAINT SERVICES

WB1018 100% ACRYLIC FLOOR FINISH

Features:

A water based 100% pure acrylic emulsion, suitable for application to all types of porous substrates, including wooden and concrete floors. Exhibits excellent water resistance.

Availability:

BS4800 colour range plus Black, White and Clear in 5 Litre containers in matt or satin finish. Can also be made in a non-slip finish.

Volume Solids:

45% ± 3% (BS 3900 Part A10).

Preparation:

The surface should be thoroughly clean, dry and free from dust and grease. Previously painted surfaces must be stripped, thoroughly rubbed down with abrasive paper and cleaned prior to application.

Application:

Brush, roller, conventional or airless spray. Supplied ready for use for brushing. Use clean tap water for thinning if required and cleaning. It is recommended that two coats be applied to previously untreated surfaces, allowing 2 hours drying between coats.

Coverage:

Approximately 50 sq metres per 5 Litres depending on porosity of substrate.

Drying:

Touch dry: 30 minutes @ 20°C.

Hard dry & recoatable: 2 hours @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.