



TECHNICAL PAINT SERVICES

WB178 WATER BASED ACRYLIC GLOSS PAINT

Features:

A water based gloss paint based on acrylic resin, affording a tough durable finish on a wide range of substrates. Also available as an anti-fungal finish. Suitable for application to wood, ferrous and non-ferrous metals, plaster, concrete and most types of plastic. Low odour, non-flammable and virtually no VOC emissions. For best results use over WBP1010 primer.

Availability:

BS4800 colour range in 5, 2.5 and 1 Litre containers.

Volume Solids:

45% ± 3% (BS 3900 Part A10).

Preparation:

Surfaces must be sound, clean, dry and free from wax, grease, oil and loose particles. Porous substrates such as plaster and plasterboard should be treated with stabilising solution before finishing. On existing painted surfaces, remove all loose and flaking paint and thoroughly rub down with abrasive paper. Any bare surfaces should be primed with suitable primer as necessary. Ensure adequate ventilation during application and drying.

Application:

Stir thoroughly and check colour before use. Apply by brush, roller or spray. When applied in areas of constant humidity, such as indoor swimming pools and conservatories, it is advisable to use Anti-Fungal Water Based Gloss. Do not apply at temperatures below 8°C or when raining or foggy.

Coverage:

Approximately 12 - 15 sq metres per Litre.

Drying:

Touch dry: 15 - 20 minutes @ 20°C.
Hard dry: 2 hours.
Recoatable: 4 hours.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.