



TECHNICAL PAINT SERVICES

WBP185 WATER BASED HIGH BUILD METAL PRIMER

Features:

A high performance, water based, high build primer incorporating a chemical rust converter which exhibits excellent adhesion to ferrous and non ferrous substrates, affording a tough, durable coating. Suitable for application to substrates prior to application of water based acrylic finishes. Also suitable for use on structural steelwork not requiring over-coating.

Availability:

5 Litre containers in Red Oxide.

Volume Solids:

85% ± 3% (BS 3900 Part A10).

Preparation:

Surfaces must be sound, clean, dry and free from wax, grease and oil. Remove all dust and loose particles. On existing painted surfaces, remove all loose and flaking paint and rub down thoroughly with abrasive paper. Any bare surfaces should be primed with a first coat.

Application:

Stir thoroughly before use. Apply by brush, roller or spray. Do not apply at temperatures below 8°C, or when raining or foggy. For spraying, thin up to 20% with clean tap water. Ensure adequate ventilation during application and drying.

Coverage:

Approximately 8 - 12 sq metres per Litre depending on application method.

Drying:

Touch dry: 1 hour @ 18°C and 65% humidity.
Recoatable: Within 4 hours.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.